



ERB-Series

Semi-Automatic Rotary Blister Sealer

The rotary, thermo-sealing machine is ideal for low to high volume production.

Features:

These machines are equipped with:

- The teflon-coated sealing head is regulated by a **digital temperature control**.
- Blisters and cards are fed and unloaded manually.
- Machine is equipped with **CAM** index drive system with speed control.
- All motions and functions are coordinated using operator interface.
- Counter is provided and can be reset for each production run.
- All functions for set-up purposes can be independently activated.
- Machine set-up is simply a question of minutes.
- Change-over of card magazine and jigs is quick and easy.
- Structure: Heavy gauge welded steel.



Optional Features:

- The machine can be equipped with self-standing **automatic card feeding**
- Automatic unloading** of finished products.

Specifications:

Model	ERB-8		ERB-6			ERB-4		
Maximum Sealing Area	14" x 18"	12" x 14"	14" x 18"	18" x 22"	12" x 14"	14" x 18"	18" x 22"	
Number of Stations	8	6			4			
Working Pressure	80 PSI							
Air Consumption CF / Cycle	1.3	.8		1.2	.8		1.2	
Electricals	220/1 or 220/3	110 or 220	220	220/1 or 220/3	110 or 220	220	220/1 or 220/3	
Amps	20 or 14	19 or 11	20	30 or 15	19 or 11	20	30 or 15	
Cylinder Bore Size (double-acting)	6"		8"		6"		8"	
Speed (max. cycles per minute)	12			10				
Dimensions	Length	100"	65"	76"	94"	65"	76"	
	Width	83"	53"	64"	82"	53"	64"	
	Height	63"						
	Working Height	37"						
Approx. Weight	850 lbs	450 lbs	500 lbs	750 lbs	400 lbs	450 lbs	650 lbs	

Note: An additional 20" of floor space is required for optional unit.
Custom sizes and features available on request.

Specifications & Designs may change without notice

Some photos may show accessories not part of basic machine
 Pricing does not include taxes, shipping & handling

HSA PACKAGING SYSTEMS

21500 Blythe Street, Canoga Park, CA 91304

Tel: (818) 712-0100; **Toll Free: (800) 326 5937**; Fax: (818) 712-0470

Email: sales@hsapackaging.com; Web: www.hsapackaging.com